



Z-Pile[®] CF[®]

sheet-pile.com/zpile





100% melted and manufactured in the USA
BABA2021 Compliant




Configuration A



Wadit® Factory Installed
Comes tack-welded and driven as one unit.

SECTION NAME:

18 - 2146



Section width in mm

Section modulus (elastic) in $\text{cm}^3/\text{m} \div 100$

These are examples from a large variety of possible Z-Pile® solutions.

Please configure your own system on sheet-pile.com/zpile

Sheet Pile LLC is the owner and assignee of numerous patents and IP, that may be related to this sheet pile solution.



100% melted and manufactured in the USA
BABA2021 Compliant

Z-Pile® CF®

sheet-pile.com/zpile



Section	Solution Type	Width	Depth	Web Thickness	Flange Thickness	Panel Cross Section Area	Panel Weight	Panel Moment of Inertia	Panel Section Modulus	Coating Area	Coating Area Waterside	Weight	Moment of Inertia	Section Modulus	Configuration
		in (mm)	in (mm)	in (mm)	in (mm)	in ² (cm ²)	lb/ft (kg/m)	in ⁴ (cm ⁴)	in ³ (cm ³)	ft ² /ft (m ² /m)	ft ² /ft (m ² /m)	lb/ft ² (kg/m ²)	in ⁴ /ft (cm ⁴ /m)	in ³ /ft (cm ³ /m)	
16-2146	Z	84.5	24.4	0.3	0.3	35.55	121	2508.8	208.5	18.64	9.32	17.2	356.3	29.6	A
		2146	621	8	8	229.36	180	104425.4	3415.9	5.68	2.84	83.9	48660.5	1591.8	
18-2146	Z	84.5	24.5	0.3	0.3	39.11	133.1	2856.5	236.1	18.64	9.32	18.9	405.7	33.5	A
		2146	622	8	8	252.33	198.1	118896.9	3868.6	5.68	2.84	92.3	55404	1802.7	
19-2146	Z	84.5	24.5	0.3	0.3	40.7	138.5	2976.4	245.5	18.64	9.32	19.7	422.7	34.9	A
		2146	622	8.3	8.3	262.6	206.1	123885.5	4022.3	5.68	2.84	96.1	57728.6	1874.3	
20-2146	Z	84.5	24.5	0.3	0.3	42.65	145.1	3118.9	257.2	18.64	9.32	20.6	443	36.5	A
		2146	622	8.7	8.7	275.13	216	129819.3	4214.9	5.68	2.84	100.6	60493.6	1964.1	

Specifications

When using steel sheet pile, it is necessary to make allowances for deviations from theoretical exactness. The degree of precision obtainable in the production of sheet pile is limited by the basic character of the rolling processes and normal limitations of mill equipment. Care must be taken during installation to assure that each element is being set at the desired driving dimension.

- Dimensions typically shown are nominal.
- Actual thicknesses vary due to mill rolling practices; however, permitted variations for such dimensions are not addressed.
- Interlocks should be reasonably free-sliding when threaded.
- Terms, tolerance, dimensions, and delivery conditions are in accordance with EN 10248 and/or ASTM A6.
- Welding is in accordance with AWS D1.1.

	AMERICAN ASTM A 6		EUROPEAN EN 10248
Mass	5%	-2.5%	± 5%
Length	+ 5in.	-0 in.	± 200mm
Height			± 7mm
Thickness			± 0.5mm for ≤ 8.5mm ± 6% for > 8.5mm
Width Interlocked			± 3%
Straightness			0.2% of the length
Ends ou of Square			2% of the width

Available Steel Grades

AMERICAN			CANADIAN			EUROPEAN		
ASTM	YIELD STRENGTH		CSA G40.21	YIELD STRENGTH		EN 10248	YIELD STRENGTH	
	(ksi)	(MPa)		(ksi)	(MPa)		(ksi)	(MPa)
A 328	39	270	Grade 260 W	38	260	S 240 GP	35	240
A 572 Grade 42	42	290	Grade 300 W	44	300	S 270 GP	39	270
A 572 Grade 50	50	345	Grade 355 W	50	350	S 320 GP	46	320
A 572 Grade 55	55	380	Grade 400 W	58	400	S 355 GP	51	355
A 572 Grade 60	60	415				S 390 GP	57	390
A 572 Grade 65*	65	450				S 430 GP	62	430
A 588 Grade 50	50	345				S 450 GP*	65	450
API 5L x70	70	485						
ASTM A 690 MARINER®	50	345						

ENGINEERING DISCLAIMER

This publication contains information on the properties of hot-rolled sheet pile based on accepted engineering practices related to sheet pile products and projects. The use of the data contained herein must be supplemented with qualified professional judgment.

LEGAL DISCLAIMER

“The information, including technical and engineering data, figures, tables, designs, drawings, details, suggested procedures, and suggested specifications, presented in this publication are for general information only. While every effort has been made to ensure its accuracy, this information should not be used or relied upon for any specific application without independent competent professional examination and verification of its accuracy, suitability and applicability.

Anyone making use of the material does so at their own risk and assumes any and all liability resulting from such use. **SHEET PILE LLC DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY FITNESS FOR ANY GENERAL OR PARTICULAR PURPOSE OR FREEDOM FROM INFRINGEMENT OF ANY PATENT, TRADEMARK, OR COPYRIGHT IN REGARD TO INFORMATION OR PRODUCTS CONTAINED OR REFERRED TO HEREIN.** Nothing herein contained shall be construed as granting a license, express or implied, under any patents.

These brands and products are supplied exclusively by or through Sheet Pile LLC.



Toll free: 866.666.7453 | +1 512.243.1228 | info@sheet-pile.com | sheet-pile.com

© 2026 Sheet Pile LLC. All rights reserved.